

## Round

QUALIKO

24 Volt  
Safety Voltage

Tipo	Referência	Dimensões (mm)	Cor	°Kelvin	Lumen	Potência (W)	Diâmetro do furo (mm)
ROUND 95 NW	BD09524TNW0B	Ø 95 x28h	Branco Natural	4200°K	180	5	Ø 80
ROUND 95 WW	BD09524TWW0B	Ø 95 x28h	Branco Quente	3000°K	170	5	Ø 80
ROUND 140 NW	BD14024TNW0B	Ø 140 x28h	Branco Natural	4200°K	280	7	Ø 120
ROUND 140 WW	BD14024TWW0B	Ø 140 x28h	Branco Quente	3000°K	250	7	Ø 120
ROUND 170 NW	BD17024TNW0B	Ø 170 x31h	Branco Natural	4200°K	550	10	Ø 145
ROUND 170 WW	BD17024TWW0B	Ø 170 x31h	Branco Quente	3000°K	520	10	Ø 145
ROUND 200 NW	BD20024TNW0B	Ø 200 x31h	Branco Natural	4200°K	600	12	Ø 180
ROUND 200 WW	BD20024TWW0B	Ø 200 x31h	Branco Quente	3000°K	580	12	Ø 180
ROUND 275 NW	BD27524TNW0B	Ø 275 x31h	Branco Natural	4200°K	1150	19	Ø 250
ROUND 275 WW	BD27524TWW0B	Ø 275 x31h	Branco Quente	3000°K	1100	19	Ø 250
ROUND 330 NW	BD33024TNW0B	Ø 330 x31h	Branco Natural	4200°K	1350	23	Ø 310
ROUND 330 WW	BD33024TWW0B	Ø 330 x31h	Branco Quente	3000°K	1300	23	Ø 310

## Downlight LED Round

- Estrutura em alumínio pintado
- Excelente homogeneidade
- Extra fino 28÷31 mm
- Funciona a 24 DC com transformadores específicos para led
- Consumo reduzido